



65/1 Moo 8 Nongphalai, Banglamung,


Chonburi 20150 THAILAND

Tel. +6638-702-297 Fax. +6638-703156

www.thaifrance.com

manager@thaifrance.com

Home /office Security Alarm System 10 June 09

	<p>Model No: SS-2003D Price: /199\$ /set Intruder alarm system Basic Component: One host +one PIR +one door detector +two remotes +one siren Installation in your home 2000 to 2500 baths</p>
<p>Features: (SS-2003D)</p> <ol style="list-style-type: none"> 1. 10 second call auto-answer message auto-memorize and auto-reply. 2. Pone alarm: 6 lines phone auto-alarm 3. Emergency phones, includes mobile 4. 32 wireless protecting code zones 5. Password protecting: set up entering password 6. Wireless transmission in case of telephone lines failure. 7. Long distance control, monitor, talk to & alarm message replay function by phone/mobile 8. Emergency alarm: controller include emergency button. 9. Power off protection, built-in high power standby battery. 10. Multi arm and alarm work state optional. 11. Sub-area arm/disarm: can set up a part zone effectually by remote controller such as night being invalid in the room, the windows and doors are effective. 12. Power Voltage: AC220V~DC12V 13. Built-in 120db siren can be connected with loudhailer. 14. Memory function: record alarm messages etc. 	

15. Smoke detector automatically sounding a warning to people when they sense smoke or other products of combustion.

Technique Parameter:

Host Current Standby:<35mA, Alarm: <150mA

Magnetic Switch's radio frequency: 310MHz(±75MHZ)

Working temperature: -10□~55□.

Overall size: 150x145x35mm.



Model No:SS-2003C

Price & term: /280\$/set

Intruder alarm system

Basic Component:

One host +one PIR +one door detector

+three remotes +one siren+ one adapter

Installation in your home 2500 to 3000
baths

Features: (SS-2003C)

1. Zone display: LED digital display, indicates zone of intrusion
2. 10 seconds voice record function
3. 6 zone capability: pre-stored alarm event such as fire-alarm, intrusion, gas leakage.
4. 6 groups lines alarm automatically: the main unit will advise alarm status and also display the alarm zone
5. Power off protection: all input data including pin codes will not be affected in a power failure
6. Separate arm and delay arm function
7. Recognize alarm events: can inform through telephone the cause of alarm i.e. intrusion, fire, gas or smoke by number of beeps.
8. Remote access function, remote arm, disarm, start up siren etc
9. Easy to add on additional detectors if required
10. Anti-tamper function: the alarm will activate if the telephone wire is cut off
11. Code protection: all actions cannot be processed without the correct code; you can change the code any time.
12. Dial to extension number, or extension number dialing out for alarming
13. Standby batteries
14. Network function, the first telephone must be the monitor center

Technique Parameter:

Host Current standby: <35mA, alarm: <150mA.

Magnetic Switch's radio frequency: 310MHz(±75MHZ)

Working temperature: -10□~55□.

Overall size: 150x145x35mm.



Model:SS-2003F

Price & term: /399\$

set

Home alarm system with voice instruction and LCD display

Basic Component:

One host +one PIR +one door detector
+three remotes +one siren

Installation in your home 3000 to 3500
baths

Features: (SS-2003F)



1. Blue LCD digital display feature
2. Handle process have English menu display, key and voice clew, easy to handle
3. Blue LCD display, clock data real time display, handle content and work estates clarity and simple
4. History record include time, main host states, handle content or alarm kind and many importance information, Don't lost forever .
5. Exceed zone have 128 wireless zone
6. Wireless detector has self-inspection feature and send information to main unit about work working status, daily maintenance more convenience.
7. Network feature: can be used as single unit and also can contact with monitor center
8. Arm, away-arm, away mute arm, stay arm function keys for choice
9. Alarm priority function, can first dial-up alarm function
10. Each zone can be set in activate or deactivate status respectively
11. Each detector can be set independence.
12. Each detector can be set if have destroy detector alarm function
13. Optional voice alarm and mute alarm for spot area
14. Built-in AC adapter and rechargeable battery.
15. When alarm the most unit used English voice told you the alarm area, alarm zone and what kind of alarm (fire, gas and so on)





Main Functions:

1. Alertness: when intruder trigger the sensor or the system sense the alert from gas alarm, smoke alarm, it will start up the siren at spot area, at the same time, dial the preset police's telephone or give the monitor center a alert information automatically.
2. 128 wireless zone alarm: detector log in main host automatically, user can define alarm type. Every wireless zone can be set away-arm and stay-arm.
3. 9 groups telephone alarm: when unite alarm, the first number must be the phone number of the monitor station, others 8numbers are normal phone number or mobile phone.
4. Alarm disposal: when pick up telephone, you can hear the voice about the alarm place, alarm style and 20 seconds spot listen-in, you can replay the alarm record, start the siren, can deactivate this alarm and switch on arm, disarm.
5. Message recording: the host can keep record for 100pcs message for arm, away-arm, mute arm, stay arm, convenient for anytime inquire and alarm affair disposal.
6. Remote assess function: with remote telephone to dial the phone number in the host, after password confirmation, you can process disarm, arm, start the siren and spot listen in
7. Arm and disarm: you can arm and disarm by the remote controller or the panel , or telephone from outside, can select to send the arm /disarm message to the monitor center or not

8. Priority alarm function: no matter calls in or out or busy, the main host will firstly dial out for alarming.
9. Intellectualized voice alarm function: user can record the address for 12 seconds , additional 2.2 seconds for 1-9 zones, other 40 seconds for recording alarm zone alarm events.
10. Transform between AC and DC automatically: when the power cut off, the DC stand by battery will continue to work to make sure the normal working.
11. Spare power: when the power supply becomes low ,the LCD display “low power”, the buzzer emit “buzz” alarm voice, main host will alarm. After one hour the system will stop power supply
12. Selected anti-tamper function: If the telephone line is cut off, the siren will alarm automatically. This function can be closed as user’s requirement
13. Extension alarm: can use direct line and extension line to preset the phone numbers. The system can set 1-3 exterior coding, the direct line can automatism identify.

Accessories alarm for main unit 10 June 09

ITEM /Model	PICTURE	SPECIFICATIONS	
wireless PIR SS100D-HW		<ol style="list-style-type: none"> 1)Working power: 9V battery 2),Frequency:433/315MHZ 3) Working environment: -10 - 50 4)Transmission distance: : >100m 	44\$
wireless Rooftop PIR -SS100A-HW		<ol style="list-style-type: none"> 1.Power supply: 9VDC 2, frequency 315MHz or 433MHz, 3.Transmitting distance >150 m (wide area without interfere) 	56\$
wireless ,Door sensor -SS200-MC		<ol style="list-style-type: none"> 1. Triggered distance :< 1.5cm 2. Working voltage12V DC, dry battery model:23A . 3. Working current : ≤10mA 4. Static current : ≤5μA 6. Transmitting distance : ≥100m 	14\$
wireless Roller Shutter Detector -SS100-CC		<ol style="list-style-type: none"> 1. Triggered distance :< 6 cm 2. Working voltage12V DC, dry battery model:23A 4. Frequency: 433/ 315 MHZ 5. Transmitting distance : ≥100m ; 	43\$

wireless .Panic Button --SS-01B		1. Working voltage 12V DC, dry battery model: 23A 2. frequency : 433/ 315 MHZ	14\$
11. Outdoor PIR detector SS100H-HW01		Features: A. Microwave and infrared double detection, highly accurate. Only gives alarm to real body movement. B. Adopting patented full-scope precision temperature compensation, the detecting sensitivity is always stable and consistent within working temperature despite temperature changes. Can connect only with model ss2003F	199\$
smoke detector -SS100A-YG		1. Power source: DV9V 2. Static current: <6.5uA 3. Alarm Current: 10mA 4. Alarm volume: >85db(3m) 5. Low voltage alarm: 6.8v~7.2v 6. no need connection with alarm system unit	40\$
wireless Strobe Alarm -SC-103		1- Operating Range: 6-15 2- Rated current: 300 3- Rated Voltage (VDC): 12 4- SPL: 110±3 5. must to order for ss2003D/ss2003C Model ss2003F must to have transformer 12v ad /21\$/ euros	22\$

Conditions of sale

All models of alarm unit is 1 year Guarantee, except if the body case was opened by the customer

All models of accessories is 6 months Guarantee.

Guarantee is include parts and labor work in the headquarters of our company ,in this case we exchange free of charge or we send back to the factory for repair .



All our alarm system are build to norm CE in conformity